

T-PAK 500

HIGH SPEED BAG SEALING SYSTEM

OK
oksealer.com



The T-Pak 500 is a flat bed conveyor combined with a Supersealer and optional T-Pak infeed, SST Trimmer and Trim Remover. This system is used in combination with automatic baggers or multi operators on one line. It comes in painted or stainless and washdown configurations.

OKSEALER.COM



TECHNICAL SPECIFICATIONS T-PAK 500:

Bag size range:	All bag sizes
Standard features:	Product placement on the main conveyor is aided by a guide and bag top guide
Finish:	Powder coating standard, stainless steel optional
Speed:	Variable to match Supersealer
Machine handling:	Right to left or left to right
Electric:	110 VAC, 1 Ph, 60 Hz, 10 Amp or 220 VAC, 1 Ph, 50 Hz, 7 Amp or to requirement CE components
Pneumatic:	Not required for standard configuration Required for optional jet flow trim remover
Belt length:	10' or 3 meters. Other sizes on request
Belt width:	16" /406mm or 18" /457mm. Other sizes on request



FEATURES:

BENEFITS:

Supersealer bag sealer:	Superior performance for many years
Automatic bag presentation:	Optimum seal quality and aesthetics
Modular design with individual frames on wheels:	Mobility and easy access for maintenance
Stainless steel construction optional:	Ideal for use in food processing plants and harsh environments

T-PAK 500 OPTIONS:

- Bag top trimmers and trim removers
- Ink jet printers
- Motorized pedestal
- T-Pak in-feed
- Automatic bag loaders

T-Pak 500 machine drawing. Drawing dimensions as reference ONLY.

