

T-PAK 750

HIGH SPEED BAG SEALING SYSTEM

OK
oksealer.com



The T-Pak 750 is an angled bed conveyor combined with a supersealer and optional T-Pak infeed, SST Trimmer and Trim Remove. This system is used in combination with automatic baggers or multi operators on one line. It comes in painted or stainless steel and washdown configurations.

OKSEALER.COM



TECHNICAL SPECIFICATIONS T-PAK 750:

Bag size range:	All bag sizes
Standard features:	Product placement on the main conveyor is aided by a back belt and bag top guide
Finish:	Powder coating standard, stainless steel optional
Speed:	Variable to match Supersealer
Machine handling:	Right to left or left to right
Electric:	110 VAC, 1 Ph, 60 Hz, 10 Amp or 220 VAC, 1 Ph, 50 Hz, 7 Amp or to requirement CE components
Pneumatic:	Not required for standard configuration Required for optional jet flow trim remover
Belt length:	10' or 3 meters. Other sizes on request
Belt width:	16"/406mm or 18"/457mm. Other sizes on request



FEATURES:

BENEFITS:

Supersealer bag sealer:	Superior performance for many years
High speed:	One system meets needs of one or many operators or high speed automatic bagger
Minimal power requirement:	Low utility consumption. Meets needs for green
Custom systems:	Systems to meet your application requirements

T-PAK 750 OPTIONS:

- Bag top trimmers and trim removers
- Ink jet printers
- Motorized pedestal
- T-Pak in-feed
- Automatic bag loaders

T-Pak 750 machine drawing. Drawing dimensions as reference ONLY.

