



PAINTED-STEEL SUPERSEALER SB10

CONTINUOUS ROTARY BAND SEALER



High-speed & Efficient

- BAND SEALING TECHNOLOGY
- OPTIMUM SEAL QUALITY & AESTHETICS
- NO TOOL BAND CHANGEOVER
- ADJUSTABLE MOTORIZED PEDESTAL
- CUSTOMIZED FOR EACH APPLICATION

Hot air sealing for a great seal at low maintenance

The Supersealer SB10 Band Sealer continuously seals a wide range of bag materials at high speed and efficiency. Constructed of heavy duty painted steel, the SB10's band sealing technology and operator friendly controls ensures continuous duty performance in demanding applications. This sealer can be customized with add-ons to add additional functions to the system.



 WATCH OUR VIDEOS
& LEARN MORE AT:
OKSEALER.COM



TECHNICAL SPECIFICATIONS:

Bag size range:	All bag sizes
Bag material range:	Heat seal materials up to 12 mils
Speed:	Up to 48 ft/min. (14.6 m/min.)
Seal width:	5/16" (8mm) up to 3/4" (19mm)
Machine handling:	Right to Left, or Left to Right
Electrical requirements:	110VAC, 1 PH, 60 Hz, 10 AMP or 220VAC, 1 PH, 50 Hz, 7 AMP CE Marked
Pneumatic requirements:	Not required on standard config. Required for optional Jet Flow Trim remover

FEATURES

BENEFITS

No tool band changeover:	Easily maintained
Variable speed:	Flexibly adjusted with speed matching conveyors
Closed loop PID temperature control:	Accurate and consistent sealing temperature
Motorized Pedestal:	With a touch of a button, height adjustments are made easily. Simplifies multiple bag/pouch applications

ADD-ON OPTIONS

- **Bag Top Trimmers:** Rotary blade or stationary blade.
- **Trim Removers:** 3" (76mm), or 5" (127mm).
- **Automatic Infeed:** T-PAK infeed into Supersealer for high-speed conveyors.
- **Air Evacuation/Gas Flush:** Bags sealed with this system extend the shelf life, and/or reduce the volume for packaging.
- **Conveyors:** Designed to meet all application requirements.
- **Bag fillers & loaders:** OKI works with scale, augers, robotics, and automatic bag loader manufacturers to create a seamless packing line.
- **Washdown/Corrosive Sealer:** Match any environment (IP65/IP69K available).
- **Dedusters:** Used in dusty environments to remove dust from seal areas.

OTHER AVAILABLE MODELS:

SUPERSEALER SS1 HOT-AIR SEALER

SS1 (Left to Right config.) is a painted supersealer with locking casters and motorized pedestal for ease of bag changeover and mobility



SUPERSEALER SB20 WITH SCALE

SUPERSEALER SB30 HEAVY-DUTY BAND SEALER

SB30 (Left to Right Config.) with casters & motorized pedestal. Equipped with optional BBY200 Conveyor.



Now with Touchscreen Display

CONTROL OPERATION, TEMPERATURE, CONVEYOR & SEALER SPEED, AND SAVE RECIPE SETTINGS FOR EASY BAG CHANGEOVER

OK International Corporation

73 Bartlett Street, Marlborough, MA 01752, USA
1-508-303-8286 | sales@oksealer.com

OK International Europe Ltd.

OK House, Shepherds Grove Industrial Estate, West Stanton, Suffolk, IP 31 2AR
England
44-1359-250705 | uksales@okcorp.com

OK Packaging Systems B.V.

Heereweg 441-a, 2161 DB Lisse, Nederland
31-252-216250 | nlsales@okpackaging.com

 **WATCH OUR VIDEOS
& LEARN MORE AT:**
OKSEALER.COM