



STAINLESS-STEEL SUPERSEALER SB20-WD

WASHDOWN CONTINUOUS ROTARY BAND SEALER



The most customizable & reliable sealers on the market

The Supersealer SB20WD is available in IP65 and IP69K rated washdown bag sealers. An IP65 rating sealer can be washed down using only a garden hose pressure. Our Supersealer SB20 band sealer is IP69K rated and can handle the demands of aggressive washdown. This system features a touchscreen control panel. The Supersealer SB20 Continuous Heat Bag Sealer continuously seals a wide range of bag materials at high speed and efficiency. The heavy-duty stainless steel construction in combination with proven band sealing technology and operator friendly controls ensures continuous duty performance in demanding applications.

High Quality & Efficient

- STAINLESS-STEEL CONSTRUCTION
- SPEEDS UP TO 48 FT/MIN
- NO TOOL BAND CHANGEOVER
- ADJUSTABLE MOTORIZED PEDESTAL
- CUSTOMIZED FOR EACH APPLICATION



 WATCH OUR VIDEOS
& LEARN MORE AT:
OKSEALER.COM



TECHNICAL SPECIFICATIONS:

Bag size range:	All bag sizes
Bag material range:	Heat seal materials up to 12 mils
Speed:	Up to 48 ft/min. (14.6 m/min.)
Seal width:	5/16" (8mm) up to 3/4" (19mm)
Machine handling:	Right to Left, or Left to Right
Electrical requirements:	110VAC, 1 PH, 60 Hz, 10 AMP or 220VAC, 1 PH, 50 Hz, 7 AMP CE Marked
Pneumatic requirements:	Not required on standard config. Required for optional Jet Flow Trim remover

FEATURES

BENEFITS

No tool band changeover:	Easily maintained
Variable speed:	Flexibly adjusted with speed matching conveyors
Closed loop PID temperature control:	Accurate and consistent sealing temperature
Motorized pedestal:	With a touch of a button, height adjustments are made easily. Simplifies multiple bag/pouch applications
IP65 or IP69K washdown unit:	Offers the choice of simple or aggressive washdown for sanitization requirements.

ADD-ON OPTIONS

- **Bag Top Trimmers:** Rotary blade or stationary blade.
- **Trim Removers:** 3" (76mm), or 5" (127mm).
- **Automatic Infeed:** T-PAK infeed into Supersealer for high-speed conveyors.
- **Air Evacuation/Gas Flush:** Bags sealed with this system extend the shelf life, and/or reduce the volume for packaging.
- **Conveyors:** Designed to meet all application requirements.
- **Bag fillers & loaders:** OKI works with scale, augers, robotics, and automatic bag loader manufacturers to create a seamless packing line.
- **Washdown/Corrosive Sealer:** Match any environment (IP65/IP69K available).
- **Dedusters:** Used in dusty environments to remove dust from seal areas.

OTHER AVAILABLE MODELS:

SUPERSEALER SB20 ROTARY BAND SEALER

SB20 (Right to Left config.) with casters and motorized pedestal. Equipped with optional BBY100 Conveyor on a motorized pedestal.



SUPERSEALER SB20 WITH SCALE

SB20 (Left to Right config.) with casters and motorized pedestal. Equipped with optional BBY100 Conveyor on a motorized pedestal and Scale.



SUPERSEALER SB30 HEAVY-DUTY BAND SEALER

SB30 (Left to Right Config.) with casters & motorized pedestal. Equipped with optional BBY200 Conveyor.



Now with Touchscreen Display

CONTROL OPERATION, TEMPERATURE, CONVEYOR & SEALER SPEED, AND SAVE RECIPE SETTINGS FOR EASY BAG CHANGEOVER

OK International Corporation

73 Bartlett Street, Marlborough, MA 01752, USA
1-508-303-8286 | sales@oksealer.com

OK International Europe Ltd.

OK House, Shepherds Grove Industrial Estate, West Stanton,
Suffolk, IP 31 2AR, England
44-1359-250705 | uksales@okcorp.com

OK Packaging Systems B.V.

Heereweg 441-a, 2161 DB Lisse, Nederland
31-252-216250 | nlsales@okpackaging.com

 **WATCH OUR VIDEOS
& LEARN MORE AT:**
OKSEALER.COM