



SUPERSEALER



PAINTED-STEEL SUPERSEALER SS1

CONTINUOUS ROTARY HOT-AIR SEALER

High-speed, great seals

- HOT-AIR SEALING TECHNOLOGY
- OPTIMUM SEAL QUALITY
- LOW MAINTENANCE
- ADJUSTABLE MOTORIZED PEDESTAL
- CUSTOMIZED FOR EACH APPLICATION

Hot air sealing for a great seal at low maintenance

The Supersealer SS1 Hot Air Bag Sealer utilizes ambient air to continuously seal a wide range of bag materials at high speed and efficiency. The advanced airflow, sophisticated controls, and rugged painted finish ensures continuous uptime performance in all applications. This sealer can be mounted on a motorized pedestal for easy height adjustments and bag changeover.



 WATCH OUR VIDEOS
& LEARN MORE AT:
OKSEALER.COM



TECHNICAL SPECIFICATIONS:

Bag size range:	All bag sizes
Bag material:	Heat sealable materials up to 10 mils
Speed:	Up to 80 ft/min (24.4 m/min)
Machine handling:	Right to Left, or Left to Right
Seal wheel width:	1/4" (6mm) standard 3/8" (9mm) optional
Electrical requirements:	110VAC, 1 PH, 60 Hz, 10 AMP or 220VAC, 1 PH, 50 Hz, 7 AMP CE Marked
Pneumatic requirements:	Not required on standard config. Required with optional Jet Flow Trim remover.

FEATURES


BENEFITS

Hot-air sealing technology:	Optimum seal quality with low maintenance.
Variable Speed:	Ease of matching conveyor speeds and flexibility.
Closed Loop PID Temperature Control:	Accurate and consistent sealing temperature.
Integrated design with locking swivel casters:	Mobility and easy access for maintenance.

OTHER AVAILABLE MODELS:

SUPERSEALER SB10 ROTARY BAND SEALER

SB10 (Left to Right config.) is a painted supersealer with locking casters and motorized pedestal for ease of bag changeover and mobility



**SUPERSEALER
WITH SCALE**
SS2 (Left to Right config.) base with casters and motorized pedestal. Equipped with optional BBY100 Conveyor on a motorized pedestal and Scale.

SUPERSEALER SB30 HEAVY-DUTY BAND SEALER

SB30 (Left to Right Config.) base with casters & motorized pedestal. Equipped with optional BBY200 Conveyor.



ADD-ON OPTIONS

- **Bag Top Trimmers:** Rotary blade or stationary blade.
- **Trim Removers:** 3" (76mm), or 5" (127mm).
- **Automatic Infeed:** T-PAK infeed into Supersealer for high-speed conveyors.
- **Air Evacuation/Gas Flush:** Bags sealed with this system extend the shelf life, and/or reduce the volume for packaging.
- **Conveyors:** Designed to meet all application requirements.
- **Bag fillers & loaders:** OKI works with scale, augers, robotics, and automatic bag loader manufacturers to create a seamless packing line.
- **Washdown/Corrosive Sealer:** Match any environment (IP65/IP69K available).
- **Dedusters:** Used in dusty environments to remove dust from seal areas.

Now with Touchscreen Display

CONTROL OPERATION, TEMPERATURE, CONVEYOR & SEALER SPEED, AND SAVE RECIPE SETTINGS FOR EASY BAG CHANGEOVER

OK International Corporation

73 Bartlett Street, Marlborough, MA 01752, USA
1-508-303-8286 | sales@oksealer.com

OK International Europe Ltd.

OK House, Shepherds Grove Industrial Estate, West Stanton, Suffolk, IP 31 2AR
England
44-1359-250705 | uksales@okcorp.com

OK Packaging Systems B.V.

Heereweg 441-a, 2161 DB Lisse, Nederland
31-252-216250 | nlsales@okpackaging.com

 **WATCH OUR VIDEOS
& LEARN MORE AT:**
OKSEALER.COM