



SUPERSEALER



STAINLESS-STEEL SUPERSEALER SS2

CONTINUOUS ROTARY HOT-AIR SEALER

Hot air sealing for a great seal at low maintenance

The Supersealer SS2 Rotary Hot Air Bag Sealer utilizes ambient air to continuously seal a wide range of bag materials at high speed and efficiency. The advanced airflow, sophisticated controls, rugged stainless-steel construction, and low maintenance requirement ensures continuous uptime performance in all applications. By using ambient air to seal the bag, there is no requirements for compressed air. This system gives customers a low maintenance and an outstanding return on investment along with the many years of uptime the machine will have.

High-speed, great seals

- HOT-AIR SEALING TECHNOLOGY
- OPTIMUM SEAL QUALITY
- LOW MAINTENANCE
- ADJUSTABLE MOTORIZED PEDESTAL
- CUSTOMIZED FOR EACH APPLICATION



 **WATCH OUR VIDEOS
& LEARN MORE AT:**
OKSEALER.COM



TECHNICAL SPECIFICATIONS:

Bag size range:	All bag sizes
Bag material:	Heat sealable materials up to 10 mils
Speed:	Up to 80 ft/min (24.4 m/min)
Machine handling:	Right to Left, or Left to Right
Seal wheel width:	1/4" (6mm) standard 3/8" (9mm) optional
Electrical requirements:	110VAC, 1 PH, 60 Hz, 10 AMP or 220VAC, 1 PH, 50 Hz, 7 AMP CE Marked
Pneumatic requirements:	Not required on standard config. Required with optional Jet Flow Trim remover.

FEATURES

BENEFITS

Hot-air sealing technology:	Optimum seal quality with low maintenance.
Variable speed:	Ease of matching conveyor speeds and flexibility.
Closed Loop PID Temperature Control:	Accurate and consistent sealing temperature.
Integrated design with locking swivel casters.:	Mobility and easy access for maintenance.

ADD-ON OPTIONS

- **Bag Top Trimmers:** Rotary blade or stationary blade
- **Trim Removers:** 3" (76mm), or 5" (127mm).
- **Automatic Infeed:** T-PAK infeed into Supersealer for high-speed conveyors.
- **Air Evacuation/Gas Flush:** Bags sealed with this system extend the shelf life, and/or reduce the volume for packaging.
- **Conveyors:** Designed to meet all application requirements.
- **Bag fillers & loaders:** OKI works with scale, augers, robotics, and automatic bag loader manufacturers to create a seamless packing line.
- **Washdown/Corrosive Sealer:** Match any environment (IP65/IP69K available).
- **Dedusters:** Used in dusty environments to remove dust from seal areas.

OTHER AVAILABLE MODELS:

SUPERSEALER SB20 ROTARY BAND SEALER

SB20 (Right to left config.) is a painted supersealer with locking casters and motorized pedestal for ease of bag changeover and mobility.



**SUPERSEALER
WITH SCALE**
SS2 (Left to right config.) with casters and motorized pedestal. Equipped with optional BBY100 Conveyor on a motorized pedestal and Scale.

SUPERSEALER SB30 HEAVY-DUTY BAND SEALER

SB30 (Left to Right Config.) base with casters & motorized pedestal. Equipped with optional BBY200 Conveyor.



Now with Touchscreen Display

CONTROL OPERATION, TEMPERATURE, CONVEYOR & SEALER SPEED, AND SAVE RECIPE SETTINGS FOR EASY BAG CHANGEOVER

OK International Corporation

73 Bartlett Street, Marlborough, MA 01752, USA
1-508-303-8286 | sales@oksealer.com

OK International Europe Ltd.

OK House, Shepherds Grove Industrial Estate, West Stanton, Suffolk, IP 31 2AR
England
44-1359-250705 | uksales@okcorp.com

OK Packaging Systems B.V.

Heereweg 441-a, 2161 DB Lisse, Nederland
31-252-216250 | nlsales@okpackaging.com

 **WATCH OUR VIDEOS
& LEARN MORE AT:**
OKSEALER.COM