



TWIN SUPERSEALERS

DUAL-SEAL BAG SEALING SYSTEM



Twice the Supersealer to double the seal.

The Twin Supersealer system is either two hot-air or band sealers. Available with an optional trimmer and trim remover and BBY200 support conveyor. The bag sealer will run up to 80 ft/min and will seal materials up to 10 mils. This system is recommended for the applications who requires a double seal. It comes with two motorized pedestals and stainless-steel base with locking casters. With a touch of a button, you can effortlessly change the height of the sealers.

High-speed, great seals

- HOT-AIR OR BAND SEALING SYSTEM
- OPTIMUM SEAL QUALITY
- LOW MAINTENANCE
- ADJUSTABLE MOTORIZED PEDESTAL
- CUSTOMIZED FOR EACH APPLICATION



 WATCH OUR VIDEOS
& LEARN MORE AT:
OKSEALER.COM



HOT-AIR TECHNICAL SPECIFICATIONS:

Bag size range:	All bag sizes
Bag material:	Heat sealable materials up to 10 mils
Speed:	Up to 80 ft/min (24.4 m/min)
Machine Handling:	Right to Left, or Left to Right
Seal wheel width:	1/4" (6mm) standard 3/8" (9mm) optional
Electrical Requirements:	110VAC, 1 PH, 60 Hz, 10 AMP or 220VAC, 1 PH, 50 Hz, 7 AMP CE Marked
Pneumatic Requirements:	Not required on standard config. Required with optional Jet Flow Trim remover.

BAND SEALER TECHNICAL SPECIFICATIONS:

Bag size range:	All bag sizes
Bag material range:	Heat seal materials up to 10 mils
Speed:	Up to 48 ft/min. (14.6 m/min.)
Seal width:	5/16" (8mm) up to 3/4" (19mm)
Machine Handling:	Right to Left, or Left to Right
Electrical Requirements:	110VAC, 1 PH, 60 Hz, 10 AMP or 220VAC, 1 PH, 50 Hz, 7 AMP CE Marked
Pneumatic Requirements:	Not required on standard config. Required for optional Jet Flow Trim remover

FEATURES

BENEFITS

Hot-air sealing technology:	Optimum seal quality with low maintenance.
Manual bag presentation:	Optimum seal quality and aesthetics.
Low maintenance requirement:	Consistent up-time.
Integrated design with locking swivel casters.:	Mobility and easy access for maintenance.
Stainless-steel construction:	Ideal for use in food processing plants and harsh environments.

FEATURES

BENEFITS

No tool band changeover:	Easily maintained
Variable speed:	Flexibly adjusted with speed matching conveyors
Closed loop PID temperature control:	Accurate and consistent sealing temperature
Motorized Pedestal:	With a touch of a button, height adjustments are made easily. Simplifies multiple bag/pouch applications

ADD-ON OPTIONS

- **Bag Top Trimmers:** Rotary blade or Stationary Blade
- **Trim Removers:** 3" (76mm), or 5" (127mm).
- **Automatic Infeed:** T-PAK infeed into Supersealer for high-speed conveyors.
- **Air Evacuation/Gas Flush:** Bags sealed with this system extend the shelf life, and/or reduce the volume for packaging.
- **Conveyors:** Designed to meet all application requirements.
- **Bag fillers & loaders:** OKI works with scale, augers, robotics, and automatic bag loader manufacturers to create a seamless packing line.
- **Washdown/Corrosive Sealer:** Match any environment, IP65 or IP69K available.
- **Dedusters:** Used in dusty environments to remove dust from seal areas.

Now with Touchscreen Display

CONTROL OPERATION, TEMPERATURE,
CONVEYOR & SEALER SPEED, AND SAVE
RECIPE SETTINGS FOR EASY BAG CHANGEOVER

OK International Corporation

73 Bartlett Street, Marlborough, MA 01752, USA
1-508-303-8286 | sales@oksealer.com

OK International Europe Ltd.

OK House, Shepherds Grove Industrial Estate, West Stanton, Suffolk, IP 31 2AR
England
44-1359-250705 | uksales@okcorp.com

OK Packaging Systems B.V.

Heereweg 441-a, 2161 DB Lisse, Nederland
31-252-216250 | nlsales@okpackaging.com



**WATCH OUR VIDEOS
& LEARN MORE AT:**

OKSEALER.COM