SUPERSEALER SB20WD ROTARY CONTINUOUS BAND SEALER







The Supersealer SB20 WD Continuous Heat Bag Sealer continuously seals a wide range of bag materials at high speed and efficiency. The heavy duty SB20WD stainless steel construction in combination with proven band sealing technology and operator friendly controls ensures continuous duty performance in demanding applications.

OKSEALER.COM



TECHNICAL SPECIFICATIONS SUPERSEALER SB20WD:

| Bag size range: | All bag sizes |
|------------------------|---|
| Bag material range: | Heat sealable materials up to 24 mils |
| Speed: | Up to 65 fpm or 20 mpm |
| Seal width: | 5/16" or 8mm |
| Machine handing: | Right to Left or Left to Right |
| Electric Requirements: | 110 VAC, 1 Ph, 60 Hz, 10 Amp or |
| | 220 VAC, 1 Ph, 50 Hz, 7 Amp |
| | CE marked |
| Pneumatic: | Not required on standard configuration |
| | Required for optional jet flow trim remover |

FEATURES

BENEFITS

| No tool band change over: | Easy to maintain |
|--------------------------------------|--|
| Variable speed. | Ease of matching conveyor speeds and flexibility |
| Closed loop PID temperature control: | Accurate and consistent sealing temperature |
| Motorized pedestal: | With a touch of a button, for height adjustments, simplifying multiple bag/pouch applications |

SUPERSEALER SB20WD OPTIONS:

| Bag top trimmers: | Two styles: Rotary blade or stationary blade, meeting all application requirements |
|---|--|
| Trim removers: | 3" or 76mm or 5" or 127mm Other lengths of trim can be accommodated |
| Automatic infeed: | T PAK infeed into Supersealer for high speed conveyor systems |
| Bag coders and printers: | Emboss coder or ink roll coder. Up to two lines. All other coders on the market can be mounted and integrated with the Supersealer |
| Conveyors: | Conveyors to meet all application requirements |
| Bag fillers and bag loaders: | OK International works with their partners who manufacture scales, augers, and robotics and automatic bag loaders to create a seamless packing line |
| Washdown sealer and corrosive washdown: | Upgrades for all kinds of environments and applications. Available in IP65 and IP69K |
| Deduster for difficult dusty environments: | Removes dust that creates barriers for sealing from seal area so that bag can be sealed |





SUPERSEALER SB20 WITH TRIDYNE SCALE

Supersealer SB20 (Left to Right) Base with Casters & Motorized Pedestal with Optional BBY-100 Conveyor and Scale F-206 from Tridyne.



OK International Europe Ltd. OK House Shepherds Grove Industrial Estate West Stanton, Suffolk, IP 31 2AR England 44-1359-250705 44-1359-250165 sales@okiuk.com



OK International Corporation 73 Bartlett Street Marlborough, MA 01752 USA 1-508-303-8286 1-508-303-8207 sales@oksealer.com

