

# T-PAK 550-2 HIGH SPEED BAG SEALING SYSTEM

**OK**  
oksealer.com



The T-PAK 550-2 Bag Compression and Sealing System is a high quality system for increasing bag handling and sealing output. The combination of a heavy duty conveyor system with a full width compression belt and the Band Supersealer Platform or Hot Air Supersealer Platform makes this an unchallenged heat sealing system for many applications, superior in performance and speed with low maintenance cost.

**OKSEALER.COM**



### TECHNICAL SPECIFICATIONS T-PAK 550-2:

Bag size range:	All bag sizes
Standard features:	Product placement on the main conveyor is aided by a guide and bag top guide
Finish:	Stainless steel
Speed:	Variable to match Supersealer
Machine handling:	Right to left or left to right
Electric:	110 VAC, 1 Ph, 60 Hz, 20 Amp or 220 VAC, 1 Ph, 50 Hz, 10 Amp or to requirement CE components
Pneumatic:	Not required for standard configuration Required for optional jet flow trim remover
Belt length:	Custom upon request
Belt width:	Custom upon request



### FEATURES:

### BENEFITS:

Supersealer bag sealer:	Superior performance for many years
Automatic bag presentation:	Optimum seal quality and aesthetics
Full compression belt:	Removes excess air from the bags
Modular design with individual frames on wheels:	Mobility and easy access for maintenance
Stainless steel construction :	Ideal for use in food processing plants and harsh environments

### T-PAK 550-2 OPTIONS:

- Bag top trimmers and trim removers
- Ink jet printers
- Motorized pedestal

T-Pak 550 -2 machine drawing. Drawing dimensions as reference ONLY.

