

# SUPERSEALER SB20

## ROTARY CONTINUOUS BAND SEALER

**OK**  
oksealer.com



The Supersealer SB20 Continuous Heat Bag Sealer continuously seals a wide range of bag materials at high speed and efficiency. The heavy duty SB20 stainless steel construction in combination with proven band sealing technology and operator friendly controls ensures continuous duty performance in demanding applications.

[OKSEALER.COM](http://OKSEALER.COM)



## TECHNICAL SPECIFICATIONS SUPERSEALER SB20:

Bag size range:	All bag sizes
Bag material range:	Heat sealable materials up to 24 mils
Speed:	Up to 65 fpm or 20 mpm
Seal width:	5/16" or 8mm
Machine handing:	Right to Left or Left to Right
Electric Requirements:	110 VAC, 1 Ph, 60 Hz, 10 Amp or 220 VAC, 1 Ph, 50 Hz, 7 Amp CE marked
Pneumatic:	Not required on standard configuration Required for optional jet flow trim remover

## FEATURES

## BENEFITS

No tool band change over:	Easy to maintain
Variable speed:	Ease of matching conveyor speeds and flexibility
Closed loop PID temperature control:	Accurate and consistent sealing temperature
Motorized pedestal:	With a touch of a button, for height adjustments, simplifying multiple bag/pouch applications
Touchscreen	Ease of temperature and speed

## SUPERSEALER SB20 OPTIONS:

Bag top trimmers:	Two styles: Rotary blade or stationary blade, meeting all application requirements
Trim removers:	3" or 76mm or 5" or 127mm Other lengths of trim can be accommodated
Automatic infeed:	T PAK infeed into Supersealer for high speed conveyor systems
Bag coders and printers:	Emboss coder or ink roll coder. Up to two lines. All other coders on the market can be mounted and integrated with the Supersealer
Conveyors:	Conveyors to meet all application requirements
Bag fillers and bag loaders:	OK International works with their partners who manufacture scales, augers, and robotics and automatic bag loaders to create a seamless packing line
Washdown sealer and corrosive washdown:	Upgrades for all kinds of environments and applications
Deduster for difficult dusty environments:	Removes dust that creates barriers for sealing from seal area so that bag can be sealed

**SUPERSEALER SB20WD**  
SB20WD (Right to Left) base with casters & motorized pedestal with optional BBY-600WD conveyor.

**SUPERSEALER SB20 WITH TRIDYNE SCALE**  
Supersealer SB20 (Left to Right) Base with Casters & Motorized Pedestal with Optional BBY-100 Conveyor and Scale F-206 from Tridyne.

**SUPERSEALER SB30**  
SB30 (Left to Right) base with casters & motorized pedestal with optional BBY-200 conveyor.

OK International Europe Ltd.  
OK House  
Shepherds Grove Industrial Estate West  
Stanton, Suffolk, IP 31 2AR  
England  
44-1359-250705  
44-1359-250165  
sales@okiuk.com



OK International Corporation  
73 Bartlett Street  
Marlborough, MA 01752  
USA  
1-508-303-8286  
1-508-303-8207  
sales@oksealer.com