

SUPERSEALER SS2WD

ROTARY CONTINUOUS WASHDOWN HOT AIR BAG SEALER



The Supersealer SS2WD Rotary Hot Air Bag Sealer utilizes hot air to continuously seal a wide range of bag materials at high speed and efficiency. The advanced airflow, sophisticated controls and stainless construction ensures continuous uptime performance in all applications. The Supersealer SS2WD is the only washdown bag sealer on the market. The Supersealer SS2 Washdown Hot Air Sealer is available in a IP65 or IP69K rated bag sealer. An IP65 rated bag sealer can be washed down with a garden hose pressure only. Our IP69K bag sealer or system can handle the demands of aggressive washdown.



TECHNICAL SPECIFICATIONS SUPERSEALER SS2WD:

Bag size range:	All bag sizes
Bag material:	Heat sealable materials up to 10 mils
Speed:	Up to 80 fpm or 24.4 mpm
Seal wheels:	1/4" or 6mm standard 3/8" or 9mm
Machine handling:	Right to Left or Left to Right
Electric requirements:	110 VAC, 1 Ph, 60 Hz, 10 Amp 220 VAC, 1 Ph, 50 Hz, 7 Amp. CE marked
Pneumatic:	Not required on standard configuration. Required for optional jet flow trim remover
Touchscreen:	Ease of temperature and speed

FEATURES

Hot air sealing technology:	Optimum seal quality with low maintenance
Variable speed:	Ease of matching conveyor speeds and flexibility
Closed loop PID Temperature control:	Accurate and consistent sealing temperature
Motorized pedestal:	With a touch of a button, for height adjustments, simplifying multiple bag/pouch applications

BENEFITS

OTHER AVAILABLE MODELS:

T-PAK 550 WITH SUPERSEALER
 Combined with SST bag top trimmer, 3" trim remover, flat bed conveyor and 4" foam compression belt.
 T-PAK 550 with Supersealer SS2

Combined with SST bag top trimmer, 3" jet flow trim remover, angled bed conveyor with 3" back belt.
 T-PAK 750 WITH SUPERSEALER

OKSEALER.COM

OTHER AVAILABLE MODELS:

SUPERSEALER SS1 (RIGHT TO LEFT), BASE WITH CASTERS, MOTORIZED PEDESTAL AND OPTIONAL BBY-100 CONVEYOR

SUPERSEALER SS2WD OPTIONS:

Bag top trimmers:	Two styles: Rotary blade or stationary blade, meeting all application requirements
Trim removers:	3" or 76mm 5" or 127mm Other lengths of trim can be accommodated
Automatic infeed:	T Pak infeed into Supersealer for high speed conveyor system
Bag coders and printers:	Emboss coder or ink roll coder. Up to two lines. All other coders on the market can be mounted and integrated with the Supersealer
Conveyors:	Conveyors to meet all application requirements
Medical sealer:	Calibratable and validatable. Meets today's medical industry requirements
Bag fillers and bag loaders:	OK International works with their partners who manufacture scales, augers, and robotics and automatic bag loaders to create a seamless packing line
Washdown sealer and corrosive washdown:	Upgrades for all kinds of environments and applications
Deduster for difficult dusty environments:	Removes dust that creates barriers for sealing from seal area so that bag can be sealed
Dusty environment package:	This sealer will use compressed air instead of fan to bring air to manifold and heaters. Other components changed to combat the environment

OK International Europe Ltd.
 OK House
 Shepherds Grove Industrial Estate West
 Stanton, Suffolk, IP 31 2AR
 England
 44-1359-250705
 44-1359-250165
 sales@okiuk.com



OK International Corporation
 73 Bartlett Street
 Marlborough, MA 01752
 USA
 508-303-8286
 sales@oksealer.com